

# Product data sheet

## Characteristics

# 9998L55

Contacteur, Type L, multipole lighting, remplacement bobine, 277VAC 60Hz, 8903L 2 to 6 poles, 8903LX 2 to 4 poles



### Main

Product or Component Type	Coil
Accessory / separate part destination	Class 8903 contactor

### Complementary

[Ue] rated operational voltage	277 V AC 60 Hz
Inrush power in VA	150 VA
Average consumption	30 VA
Height	2.38 in (60.5 mm)
Width	2.11 in (53.6 mm)
Depth	1.46 in (37.1 mm)

### Ordering and shipping details

Category	21756-9998 DISCOUNT CP10
Discount Schedule	CP10
GTIN	785901081241
Returnability	Yes
Country of origin	MX

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.20 in (5.6 cm)
Package 1 Width	2.91 in (7.4 cm)
Package 1 Length	3.39 in (8.6 cm)
Package 1 Weight	5.60 oz (158.8 g)

### Offer Sustainability

EU RoHS Directive	Under investigation
China RoHS Regulation	<a href="#">China RoHS Declaration</a>

### Contractual warranty

Warranty	18 months
----------	-----------