

# Product data sheet

## Characteristics

# 8910DPA42V09

Contacteur, Definite Purpose, 40A, 2 pole,  
7.5HP at 230VAC, 1 phase, 208/240VAC 60Hz  
220VAC 50Hz coil, open



### Main

Product or Component Type	Definite Purpose Contactor
Line Rated Current	40 A
Number of Poles	2P
Pole contact composition	2 NO
Range of Product	DPA

### Complementary

Maximum Horse Power Rating	3 Hp 115 V AC, 1 phase 7.5 hp 230 V AC, 1 phase
Locked rotor rated current	240 A 277 V AC 200 A 460 V AC 160 A 575 V AC
[Ue] rated operational voltage	600 V AC
[Uc] control circuit voltage	208...240 V AC 60 Hz 220 V AC 50 Hz
Phase	1 phase
Electrical Connection	Box lugs Quick connect terminals

### Environment

Product Certifications	UL Recognized[RETURN]CSA
------------------------	--------------------------

### Ordering and shipping details

Category	21344-8910 DPA 4_(40 AMP)
Discount Schedule	CP1B
GTIN	785901073468
Returnability	Yes
Country of origin	CN

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.20 in (8.128 cm)
Package 1 Width	4.00 in (10.16 cm)
Package 1 Length	2.60 in (6.604 cm)
Package 1 Weight	15.68 oz (444.521 g)
Unit Type of Package 2	CAR
Number of Units in Package 2	8
Package 2 Height	7.00 in (17.78 cm)
Package 2 Width	5.50 in (13.97 cm)

Package 2 Length	8.60 in (21.844 cm)
Package 2 Weight	8.22 lb(US) (3.729 kg)

### Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>

### Contractual warranty

Warranty	18 months
----------	-----------