

BQ2 Series


200 A 600 V; standard enclosure

Product specifications

- Conductor range: 6 AWG–250 kcmil
- Aluminum tunnel type connectors for both load and line sides
- For overhead, underground and combination overhead/underground

- Supplied with screw type ring
- Weatherproof Type 3R enclosure
- Primarily used in: All provinces

Note: Supply from an underground network often requires use of stud type connector. Consult your local utility.



Cat. no	Description	Dimensions (in.)			Weight each		
		H	W	D	lb	kg	
4 Jaw							
BQ2-V	Overhead, hub opening	15 ⁵ / ₈	8 ⁴ / ₆₄	5 ¹³ / ₃₂	12	5.4	
BQ2-VGN	Overhead opening comes with ground lug on neutral	15 ⁵ / ₈	8 ⁴ / ₆₄	5 ¹³ / ₃₂	12	5.4	
BQ2-VGN-CR	Overhead comes with ground lug on neutral, corrosion resistant	15 ⁵ / ₈	8 ⁴ / ₆₄	5 ¹³ / ₃₂	12	5.4	
BQ2-1 1/2 V	Overhead, hub opening, comes with 1½ in. hub	15 ⁵ / ₈	8 ⁴ / ₆₄	5 ¹³ / ₃₂	12	5.4	
BQ2-2V	Overhead, hub opening, comes with 2 in. hub	15 ⁵ / ₈	8 ⁴ / ₆₄	5 ¹³ / ₃₂	12	5.4	
BQ2-2VGN	Overhead, hub opening comes with 1 ½" hub and ground lug on neutral	15 ⁵ / ₈	8 ⁴ / ₆₄	5 ¹³ / ₃₂	12	5.4	
BQ2-TV	Underground	15 ⁵ / ₈	8 ⁴ / ₆₄	5 ¹³ / ₃₂	12	5.4	
BQ2-TVGN	Underground comes with ground lug on neutral	15 ⁵ / ₈	8 ⁴ / ₆₄	5 ¹³ / ₃₂	12	5.4	
BQ2-TCV	Combination, overhead-underground	15 ⁵ / ₈	8 ⁴ / ₆₄	5 ¹³ / ₃₂	12	5.4	
BQ2-TCV-CR	Combination overhead-underground, corrosion resistant	15 ⁵ / ₈	8 ⁴ / ₆₄	5 ¹³ / ₃₂	12	5.4	
BQ2-TCVGN	Combination overhead-underground comes with ground lug on neutral	15 ⁵ / ₈	8 ⁴ / ₆₄	5 ¹³ / ₃₂	12	5.4	
BQ2-TCVGN-CR	Combination overhead-underground comes with ground lug on neutral, corrosion resistant	15 ⁵ / ₈	8 ⁴ / ₆₄	5 ¹³ / ₃₂	12	5.4	
BQ2-22VNH	Overhead, twin hub opening	15 ⁵ / ₈	8 ⁴ / ₆₄	5 ¹³ / ₃₂	12	5.4	
BQ2-22VNHGN	Overhead, twin hub opening comes with ground lug on neutral	15 ⁵ / ₈	8 ⁴ / ₆₄	5 ¹³ / ₃₂	12	5.4	
BQ2-2VGN-CR	Overhead comes with ground lug on neutral, corrosion resistant	15 ⁵ / ₈	8 ⁴ / ₆₄	5 ¹³ / ₃₂	12	5.4	
BQ2-22V	Overhead, twin hub opening, comes with 2 in. hubs	15 ⁵ / ₈	8 ⁴ / ₆₄	5 ¹³ / ₃₂	12	5.4	
BQ2-22VGN	Overhead, twin hub opening comes with 2 in hubs and ground lug on neutral	15 ⁵ / ₈	8 ⁴ / ₆₄	5 ¹³ / ₃₂	12	5.4	
Factory-installed accessories							
Include:	-GN					Ground lug on neutral	
	-5					5 th jaw standard capacity	
	-6					5 th jaw full capacity, 6 o'clock position	



BQ2 Series

200 A 600 V; standard enclosure

Diagrams

