



## Main

Product or Component Type	Automatic switch
Range of Product	PowerPacT J
Trip unit technology	Magnetic
Circuit breaker type	J-frame

## Complementary

Line Rated Current	175 A
[Ue] rated operational voltage	600 V AC
Mounting Mode	Unit mount
Poles description	3P
Short-circuit withstand	65 KA 240 V UL 489 35 KA 480 V UL 489 18 kA 600 V UL 489
Breaking capacity code	G
Electrical connection	Lugs, line Lugs, load
AWG gauge	X AWG 4...AWG 4/0 ( aluminium/copper )
Terminal identifier	AL175JD
Magnetic tripping current	3125 A
Height	7.52 in (191.01 mm)
Width	2.74 in (69.60 mm)
Depth	5 in (127.00 mm)
Tightening torque	230.12 lbf.in (26 N.m) 0.04...0.15 in <sup>2</sup> (25...95 mm <sup>2</sup> ) (AWG 4...AWG 4/0)

## Environment

Product Certifications	CSA[RETURN]UL Listed[RETURN]IEC
------------------------	---------------------------------

## Ordering and shipping details

Category	01115-HG,HJ,JG,JJ UNIT MT BREAKER/SWITCH
Discount Schedule	DE2
GTIN	785901602330
Returnability	No
Country of origin	US

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.13 in (13.018 cm)
Package 1 Width	7.25 in (18.415 cm)
Package 1 Length	8.44 in (21.433 cm)
Package 1 Weight	5.77 lb(US) (2.615 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>
PVC free	Yes

## Contractual warranty

Warranty	18 months
----------	-----------