

# NMD90 CANADEX® Copper

3C6(7) NMD90 CU CANADEX

## Contact

Inside Sales Representatives  
Phone: 905-944-4300  
buildingwire.canada@nexans.com

Nexans Ref.: 12001376

Country Ref.: 649772

EAN 13: 622089106536

Residential cable

## DESCRIPTION

CSA File #LL23462 Class 5821 02

Two or three copper conductors with 90°C PVC and nylon insulation.

Bare bonding wire and overall jacket of moisture resistant and flame retardant PVC, with FT1 rating

### Nexans NMD90 CANADEX® Jacket colours:

#14 AWG - White 2 & 3C #14 for General Application

- Blue 2C#14 for Bedroom Outlets terminating at Arc Fault Circuit Interrupters

(AFCI)

#12 AWG - Yellow

#10 AWG - Orange

#8 AWG and larger - White

### NMD90 CANADEX® Insulation colours:

2 Conductors - Black, White

3 Conductors - Black, Red, White

### Residential Applications for NMD90 CANADEX® :

- For open or concealed wiring in dry or damp locations where not exposed to mechanical injury.
- Maximum conductor temperature 90°C.
- Approved for use with ceiling fixtures.
- Minimum recommended handling temperature minus 25°C for 2 conductor cables and minus 10°C for 3 conductor cables (with suitable handling procedures).

**NMD90 CANADEX® has new features available for sizes 2C14 AWG, 2C12 AWG and 3C14 AWG in colours: white, blue, yellow and red.**

Click [here](#) to learn more about the features



## STANDARDS

National CSA C22.2 N° 48

## CHARACTERISTICS

### Construction characteristics

Conductor material	Copper
Insulation	PVC/Nylon
Jacket Colour	White
With Bonding Conductor	Yes
With neutral or not	Yes

### Dimensional characteristics

Approximate net weight	600.5 kg/km
------------------------	-------------

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.

Generated 2024-06-12 [www.nexans.ca](http://www.nexans.ca) Page 1 / 2

# NMD90 CANADEx® Copper

3C6(7) NMD90 CU CANADEx

## Contact

Inside Sales Representatives  
Phone: 905-944-4300  
buildingwire.canada@nexans.com

### Dimensional characteristics

Cable Diameter	17.17 mm
Conductor size (AWG)	6 AWG
Number of cores	3
Number of strands	7

### Electrical characteristics

Maximum operating voltage	300 V
---------------------------	-------

### Usage characteristics

Maximum operating temperature	90 °C
Minimum installation temperature	-10 °C