



100A

120/240 V~ Max., 10, 50/60 Hz., 3 wires/poles

2 Poles

No overcurrent protection  
No protege contra sobrecorrientes

Main Lugs  
Zapatas principales

Indoor  
Interior

INCLUDES INCLUIDO

Molded Case Switch Included  
Incluye interruptor sin fusibles en caja moldeada

Surface  
Sobreponer

6.0 lbs / 2.7 kg  
W5.9" x H13.2" x D3.4"

Includes:  
(1) QO2000 Enclosed molded case switch, not fusible and (1) Insulated groundable neutral

QO2000NS

## Main

Product Type	Enclosed molded case switch
Range of Product	QO

## Complementary

Current Rating	100 A
Interrupt Rating	10 kA 240 V AC 50/60 Hz
Number of Poles	2P
Enclosure Rating	NEMA 1 indoor
Breaker Compatibility	Circuit breaker QO 2P
Product Certifications	UL Listed[RETURN]CSA
Mounting mode	Plug-in
Electrical Connection	Box lugs
Wire Size	AWG 4...AWG 2/0 copper or aluminium
Voltage Rating	240 V AC
Tightening Torque	4.6 N.m
Height	13.39 in (340 mm)
Width	6.14 in (156 mm)
Depth	3.50 in (89 mm)
Product Weight	6.46 lb(US) (2.930 kg)

## Ordering and shipping details

Category	00005-QO,Q2L 2P ENCL & BREAKERS
Discount Schedule	DE2A
GTIN	785901539520
Returnability	Yes
Country of origin	MX

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.61 in (11.7 cm)
Package 1 Width	7.52 in (19.1 cm)
Package 1 Length	15.00 in (38.1 cm)
Package 1 Weight	6.46 lb(US) (2.93 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations

## Contractual warranty

Warranty	18 months
----------	-----------