

TVS2HWA50X

Surge protection device, Surgelogic, HWA, 50kA, 208Y/120 VAC, 3 phase, 4 wire, NEMA 4X



Main

Product	Surge protection device
Range	Surgelogic
Device Short Name	HWA

Complementary

Surge Current	50 kA per phase
Voltage Rating	208Y/120 V AC
Number of Phases	3 phases
Wiring Configuration	4-wire
MCOV	150 V
Nominal Discharge Current	20 kA
SCCR	200 kA
Local Signalling	LED green normal operation Alarm
Height	9.4 in (238.76 mm)
Width	4.8 in (121.92 mm)
Depth	3.1 in (78.74 mm)
Cable length	33.6 in (853.44 mm)

Environment

Enclosure Rating	NEMA 4X
Standards	UL 1449:ed. 4 type II UL 1283 NEC 285 CSA C22.2 No 8 UL 96A:ed. 12
Ambient Operating	149 °F (65 °C)

Packing Units

Package 1 Weight	5.08 lb(US) (2.304 kg)
Package 1 Height	4.90 in (12.446 cm)
Package 1 width	7.40 in (18.796 cm)
Package 1 Length	10.80 in (27.432 cm)

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information