

Product data sheet

Characteristics

QOM2200VHL

Main breaker, QO, 200A, 2 pole, 120/240VAC, 22kA, bolt on mount



Main

Product	Circuit breaker
Range	QO
Current Rating	200 A
Voltage Rating	120/240 V AC 120 V AC
Mounting Type	Bolt-on
Number of Poles	2P
Circuit Breaker Type	Standard
Ratings	Primary main breaker
Electrical Connection	Lugs
Frame Size	QOM2

Complementary

Interrupt Rating	22 KA 120/240 V AC 50/60 Hz 22 kA 120 V AC 50/60 Hz
Wire Size	AWG 4...250 kcmil copper or aluminium
Tightening Torque	53.10 lbf.in (6 N.m) 0.01...0.10 in ² (4...65 mm ²) (AWG 12...AWG 2/0)
Height	5.59 in (142 mm)
Width	5.08 in (129 mm)
Depth	3.58 in (91 mm)
Net Weight	2.58 lb(US) (1.170 kg)
Load Center Type	Main breaker
Number of Phases	1 phase
For Use With	QO load center
Breaker compatibility	Load center QO

Environment

Certifications	UL Listed[RETURN]CSA
Ambient Rating	104 °F (40 °C)

Ordering and shipping details

Category	00157-CANADIAN QO CIRCUIT BKRS
Discount Schedule	DE2A
GTIN	785901372646
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.21 in (10.7 cm)
Package 1 Width	5.39 in (13.7 cm)
Package 1 Length	6.42 in (16.3 cm)
Package 1 Weight	2.58 lb(US) (1.17 kg)

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes

Contractual warranty

Warranty	18 months
----------	-----------