



### Main

Range of Product	PacDrive 3
Product or Component Type	Motion controller

### Complementary

Product Compatibility	LMC106
Number of axis	6
Discrete input number	8 digital input IEC 61131-2 Type 1 4 touch probe input IEC 61131-2 Type 1
Discrete input voltage	15...30 V - 3...5 V
Discrete input voltage type	DC
Discrete input current	4 mA digital input
Anti bounce filtering	100 µs...4.29 s configurable digital input 100 µs...4.29 s configurable touch probe input 100 µs...4.29 s configurable interrupt input
Maximum cable distance between devices	<164.04 ft (50 m)
Discrete output number	8 digital output
Discrete output current	500 mA digital output
Maximum leakage current	0.5 mA
Maximum Number of I/O Expansion Module	1
[Us] rated supply voltage	24 V DC
Power Consumption in W	30 W
Memory Type	512 MB RAM DDR2 128 kB NVRAM
Programming language	LD (ladder) ST (structured text) SFC (sequential function chart) FBD (function block diagram) CFC (continuous function chart) IL (instruction list)
Integrated connection type	2 Ethernet port RJ45 Sercos 1 Ethernet port RJ45 Ethernet 10/100BASE-T, FTP/HTTP 1 Ethernet port RJ45 master encoder 1 serial link RJ45 RS232/RS485 1 CAN port SUB-D 9 CANopen 1 USB port USB type A
Supply	Power supply 24 VDC
Width	1.73 in (44 mm)
Height	10.63 in (270 mm)
Depth	8.74 in (222 mm)
Net Weight	4.85 lb(US) (2.2 kg)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Environment

Standards	UL 508 EN/IEC 61131-2 CSA C22.2 No 142 CSA C22.2 No 14
Product Certifications	cULus[RETURN]CSA[RETURN]CE[RETURN]EAC
Ambient air temperature for operation	41...131 °F (5...55 °C)
Relative humidity	5...95 % without condensation
IP degree of protection	IP20EN/IEC 60529
Pollution degree	2 IEC 61131-2
Operating altitude	0...6561.68 ft (0...2000 m)
Vibration resistance	3.5 mm 5...8.4 Hz 10 m/s <sup>2</sup> 8.4...150 Hz
Shock resistance	150 m/s <sup>2</sup> 6 ms operation)EN/IEC 60721-3-3

## Ordering and shipping details

Category	18354-PACDRIVE3 MOTION CONTROLLERS
Discount Schedule	PC52
GTIN	3606485400310
Returnability	No

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.02 in (10.2 cm)
Package 1 Width	12.80 in (32.5 cm)
Package 1 Length	16.73 in (42.5 cm)
Package 1 Weight	4.85 lb(US) (2.2 kg)
Unit Type of Package 2	S06
Number of Units in Package 2	10
Package 2 Height	29.53 in (75.0 cm)
Package 2 Width	15.75 in (40.0 cm)
Package 2 Length	23.62 in (60.0 cm)
Package 2 Weight	13.23 lb(US) (6.0 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>
PVC free	Yes