


Galvanized Rigid Conduit (GRC) Couplings & Elbows

Galvanized Rigid Conduit (GRC) Couplings

Certified to Canadian Standards Association Safety Standard CSA C22.2 No.45.1
Manufactured in accordance with ANSI C80.1



Trade Size	Metric Designator	Nominal O.D. (A) ²		Length (B) ¹		Threads Per Inch ¹	Approximate Weight Per 100 Pieces		Standard Package
		in	mm	in	mm		lb	kg	
1/2	16	1.01	25.7	1 5/8	41.3	14	12	5.4	100
3/4	21	1.25	31.8	1 41/64	41.7	14	18	8.2	50
1	27	1.53	38.7	1 31/32	50.0	11 1/2	30	13.6	25
1 1/4	35	1.87	47.5	2 1/32	51.6	11 1/2	37	16.8	25
1 1/2	41	2.16	54.7	2 1/16	52.4	11 1/2	52	23.6	25
2	53	2.65	67.3	2 1/8	54.0	11 1/2	72	32.7	15
2 1/2	63	3.25	82.6	3 3/16	81.0	8	170	77.1	8
3	78	3.87	98.3	3 5/16	84.1	8	210	95.3	6
3 1/2	91	4.50	114.3	3 13/32	86.5	8	340	154.2	6
4	103	4.88	123.8	3 33/64	89.3	8	300	136.1	5
5	129	6.00	152.4	3 61/64	100.4	8	475	215.5	1
6	155	7.20	182.9	4 1/4	108.0	8	765	347.0	1



¹Minimum requirement as per CSA Standard


²For information only, not a requirement as per CSA Standard

Galvanized Rigid Conduit (GRC) 90 Degree Elbows

Certified to Canadian Standards Association Safety Standard CSA C22.2 No.45.1
Manufactured in accordance with ANSI C80.1



Trade Size	Metric Designator	Radius (A) ¹		Offset (B) ²		Straight (D) ¹		Approximate Weight Per 100 Pieces		Standard Package
		in	mm	in	mm	in	mm	lb	kg	
1/2	16	4	102	5 7/8	149	1 1/2	38	68	30.8	25
3/4	21	4 1/2	114	7	178	1 1/2	38	109	49.4	40
1	27	5 3/4	146	8 3/4	222	1 7/8	48	201	91.2	25
1 1/4	35	7 1/4	184	10 3/4	273	2	51	336	152.4	10
1 1/2	41	8 1/4	210	12 1/4	311	2	51	460	208.7	10
2	53	9 1/2	241	14 1/2	368	2	51	729	330.7	5
2 1/2	63	10 1/2	267	17	432	3	76	1374	623.2	80
3	78	13	330	19 5/8	498	3 1/8	79	2045	927.6	50
3 1/2	91	15	381	22 3/4	578	3 1/4	83	2860	1297.3	50
4	103	16	406	23 7/8	606	3 3/8	86	3519	1596.2	36
5	129	24	610	34 7/8	886	3 5/8	92	6942	3148.9	1
6	155	30	762	45 1/2	1156	3 3/4	95	11960	5425.1	1



¹Minimum requirement as per CSA Standard

²For information only, not a requirement as per CSA Standard

Sizes 2 1/2 (63) and larger shipped in palletized cartons or bulk.

Also available in the following Degrees (60°, 45°, 30°, 22-1/2°, 15° & 11-1/4°)

NOTE: Special orders are non-cancelable, non-returnable and non-refundable