



Main

Product	Double Throw Safety Switch
Current Rating	200 A
Certifications	CSA
Enclosure Rating	NEMA 1 galvanized steel
Disconnect Type	Non-fusible disconnect
Mounting Type	Surface
Number of Poles	3
Voltage Rating	250 V DC 480 V AC
Wire Size	AWG 6...300 kcmil copper or aluminium

Complementary

Motor power hp	15 hp at 480 V AC 50-60 Hz for 3 phase motors
Tightening torque	275 lbf.in (31.07 N.m) 0.02...0.20 in ² (13.30...127 mm ²) (AWG 6...250 kcmil)
Width	23.88 in (606.55 mm)
Height	30.88 in (784.35 mm)
Depth	11.75 in (298.45 mm)

Ordering and shipping details

Category	00153-C,CH&CHU CANADA SW NON-NEG
Discount Schedule	DE1
GTIN	785901995647
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	12.20 in (31.0 cm)
Package 1 Width	24.61 in (62.5 cm)
Package 1 Length	32.01 in (81.3 cm)
Package 1 Weight	64.99 lb(US) (29.48 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
RECh Regulation	RECh Declaration
RECh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration

RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
