



Main

Product or Component Type	Single Throw Safety Switch
Series name	General duty

Complementary

Line Rated Current	30 A
Device Composition	Neutral (factory installed)
Disconnect device type	Fusible disconnect
Short-circuit current	10 kA maximum plug
Device mounting	Surface
Number of poles	2
Electrical Connection	Lugs
[Ue] rated operational voltage	120/240 V AC
Motor power hp	0.5 Hp at 120 V AC 50-60 Hz for 1 phase motors 2 Hp at 120 V AC 50-60 Hz for 1 phase motors 1.5 Hp at 240 V AC 50-60 Hz for 1 phase motors 3 hp at 240 V AC 50-60 Hz for 1 phase motors
AWG gauge	AWG 12...AWG 6 aluminium AWG 14...AWG 6 copper
Tightening torque	30 Lbf.In (3.39 N.m) (AWG 12...AWG 6) 30 lbf.in (3.39 N.m) 0.00...0.02 in ² (2.08...13.3 mm ²) (AWG 12...AWG 6)
Height	9.25 in (234.95 mm)
Width	7.25 in (184.15 mm)
Depth	3.63 in (92.20 mm)

Environment

Product Certifications	CSA
NEMA degree of protection	NEMA 1 galvanized steel not suitable for service equipment

Ordering and shipping details

Category	00154-CD&CDU CANADA SW NON-NEGO
Discount Schedule	DE1A
GTIN	785901964315
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.20 in (13.208 cm)
Package 1 Width	7.20 in (18.288 cm)
Package 1 Length	9.20 in (23.368 cm)
Package 1 Weight	4.26 lb(US) (1.932 kg)
Unit Type of Package 2	CAR
Number of Units in Package 2	5
Package 2 Height	9.90 in (25.146 cm)
Package 2 Width	8.40 in (21.336 cm)
Package 2 Length	18.90 in (48.006 cm)
Package 2 Weight	17.50 lb(US) (7.938 kg)
Unit Type of Package 3	PAL
Number of Units in Package 3	150
Package 3 Height	40.00 in (101.6 cm)
Package 3 Width	36.00 in (91.44 cm)
Package 3 Length	48.00 in (121.92 cm)
Package 3 Weight	525.00 lb(US) (238.136 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------