Brackets, clamps, partitions



CI820-DX

CI820D

CILRW

CILA CLAMP

CISSX-6

CI1004-P

CI1104-P



CI2104-P

Cat. No.	Description
Rework support brackets	
CI820D	Device box supports. Max. wall thickness 1 in.
CI820-DX	Device box support
CILRW	For installing CI1104 series of boxes with ears, in closed wall “rework” applications. Complete with an 8-32 x 1 1/2 screw
Universal cable clamps (for BX / Loomex)	
CILA CLAMP	Supplied with screws
Support brackets	
CISSX-6	Support bracket extension for 6 in. metal stud
Device box partitions	
CI1004-P	Steel partitions for 2 in., 2 1/2 in. and 3 in. deep outlet boxes
CI1104-P*	Steel partitions for 2 1/2 in. deep gangable boxes. To be used with CI-1104 / CI-3104 Series of boxes
CI2104-P	Steel partitions for 2 in. and 2 1/2 in. deep outlet boxes

*__Note:__ Install partition while ganging boxes

In accordance with C.E.C. 2012 Edition, Rule 12-3030: Conductors that are connected to different power or distribution transformers or other different sources of voltage shall not be installed in the same box, cabinet, or fitting unless a barrier of sheet steel not less than 1.3 mm thick or a flame-retardant nonmetallic insulating material not less than 1.6 mm in thickness is used to divide the space into separate compartments for the conductors of each system.